

NUBE





























feets you.





DESCRIPTION

NUBE, this occupational clog is entirely made of polymeric materials and has the following components:

- Spillage protection device€ Evergrip™ rubber track
- Antistatic insert

SPECIFICATIONS

ventilation or superior protection that prevents the entrance of liquids into the footwear.

Evergrip™ 2 The geometric design and the chemical formula used in the production of the rubber track of this sole, provides excellent adherence to the ground reducing the risk of slipping. (SRC - Anti-slip approved).

Antistatic Promotes the dissipation of accumulated static electricity.

Breathable 4 Regulates the temperature and humidity of the

Impact Reduction 5 The footwear is produced in Everlite™, a highly flexible material that reduces the impact of walking.

Super Light 6 This shoe is produced in Everlite™, a material with great durability and comfort and is remarkably light.

TÜV This footwear was tested and approved by TÜV institue in Germany, for its anti-slip and antistatic properties.

Washable 50 °C The footwear can be machine washed up to 50°C.

Unisex Style designed to be worn by men and women.

Portuguese Shoes Footwear 100% developed and made in Portugal.

NUBE is ideal for uses where prolonged standing or walking may tend to induce foot discomfort or lower body fatigue, especially in:

Hospitals and other Healthcare Institutions **Cosmetics/Beauty Companies**

Pharmaceutical Industry Cleaning Companies

Food Industry Catering Industry

CARE AND CLEANING

Wash: Machine washable up to a maximum temperature of 50 °C. Sterilize with bleach - chlorine, sodium hypochlorite, or hydrogen peroxide. **Dry:** Wipe with a cloth or dry at room temperature.

TECHNICAL STANDARD

 (ϵ)

CE Technical file of auto-certification based on 89/696/CEE directive.

EN ISO 20347: 2012 Personal protective equipment – Occupational footwear, class II.

EN ISO 20347: 2012 (5.3.4.4) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerine - SRC

EN ISO 20347: 2012 (6.2.2.2) Antistatic footwear.

EN ISO 20347: 2012 (6.2.4) Energy absorption of seat region.

TECHNICAL SPECIFICATIONS

SRC Slip-resistant

Heat resistance - up to a maximum of 50 °C

Resistant to abrasion

Fuel oil resistant

Resistant to solvents and detergents

Resistant to Lactic Acid

Resistant to liquids (such as infiltration of blood)

Resistant to chemicals

Resistant to Saltwater

Resistant to animal fat

Recyclable

MATERIALS

The material used in this clog is called Everlite™ in its expanded form. Everlite™ material provides odor resistance, inhibits bacterial and fungal growth and is non-toxic.

ATTENTION

NUBE resists several washings at 50°C in washing machine. It is not recommended the use of bleaching agents during washing machine cycles at 50°C.

The resistance of Everlite material to washing depends on several factors:

- Type of detergent
- Concentration
- · Cycles' duration
- Temperature
- Physical stress during the cycles